



TECHNICAL SPECIFICATIONS

	GenZero 3000W	GenZero 1500W	GenZero 600W
Continuous Output	3000W	1500W	600W
Peak Output	6000W	3000W	1200W
Battery Capacity (Wh)	1540Wh	922Wh	615Wh
Battery Type	LiFePO4		
Charging Time	4 Hours	3 Hours	2 Hours
Ingress Protection	IP67		
Storage/Operating Temperature	-20 To +45		
Charge Methods	AC mains (Supplied) • Solar panel charger or Vehicle charger (Optional)		
AC Output Voltage	Select: 110V or 230V		
USB Outputs	1 x USB + 1 x USB-C		
Life Of Battery	3000+ cycles		
AC Charger Supplied	10A	10A	5A
NET Weight	31.8kg	18.2kg	12.5kg
Dimensions	579 x 465 x 297mm	505 x 409 x 257mm	429 x 328 mm x 236mm
Product Code	GZ-3000W-110V/230V	GZ-1500W-110V/230V	GENZERO-600W-110V/230V

LCD DISPLAY



- Battery capacity
- Current flow
- Battery voltage
- Discharge
- Runtime at current discharge

RCBO



RCBO RESIDUAL CURRENT BREAKER + OVER CURRENT PROTECTION

BMS PROTECTION

OVERCHARGE, OVERCHARGE DISCHARGE, TEMPERATURE/SHORT-CIRCUIT