StratoStar ECO Replacement for Petrol and Diesel <u>Tower Lights</u>



StratoStar

Rechargeable 115,000lm, Hybrid Powered Industrial Lighting Tower



	Specification
- <u>×</u> -	115,000 Lumens
	3850m ² Beam
Ū	3 - 48 Hours Runtime
MODES	High Medium Low Dimmable
	18Ah or 30Ah LifePO4 battery, 1540Wh
	8 Hours Charging time
	IP67 Rated
<u>لر</u>	Light head: 438 x 290mm
^	Batter pack: 18Ah -18.3Kg 30Ah - 23.8kg Light head: 12.7kg Tripod: 14.3kg
CODE	NSSTRATOSTAR NSSTRATOSTAR-X

Supplied with protective bags, battery pack, tripod and AC mains charger



- » Adjustable runtime up to 48 hours
- » Robust aluminium + steel tripod with hand winch and safety locks
- » 4m hand winch tripod with extendable tripod leg for uneven slopes
- » IP67 Rated, robust, high-impact housing
 - » 1540Wh LifePo4 Phosphate battery
- » Universal DIN spigot fitting (30mm DIN 14640)
 - » LCD programmable display
 - » Built-in level gauge



Features

Separates Into 3 Easy To Carry Parts Light Head - Tripod - Battery Pack Supplied in protective carry bags with carry handle and shoulder straps.



Optional accessories

400mm Ground anchors: SPGROUNDANCHORS



StratoStar Kits

W	7

OPTION 1

BATTERY AND AC 110V-240V

1 x StratoStar tower light with 4 metre tripod - Choose StratoStar 18Ah or 30Ah battery pack

KIT CODES:	NSSTRATOSTAR	StratoStar with 18Ah battery pack
	NSSTRATOSTAR-X	StratoStar with 30Ah battery pack



OPTION 2

AC MAINS POWERED ONLY

1 x StratoStar tower light with 4 metre tripod and AC adaptor

- Can be powered from GenZero or any suitable generators

KIT CODE: NSSTRATOSTAR-AC

StratoStar with AC Mains Adaptor



OPTION 3

POWERED BY GENERATOR

- Power the AC StratoStar with any generator or GenZero 1500W or 3000W power station

KIT CODES:

NSSTRATOSTAR-AC & GZ-1500W