

SIGMA ATEX 4AA Flashlight

Compact design with 3 light modes

ZONE 0



Sliding light mode switch



Features:

- ATEX certificated Gas Zone 0
- 3 Mode sliding switch
- Flashing mode ideal for signalling
- IP68 submersible up to 3 metres
- Rubberised head for extra durability
- Tough polycarbonate housing
- Impact resistant, drop proof up to 1m
- Easy operation with gloved hand
- Safety release valve to remove hydrogen gases



Safety lock to prevent from accidental operation



Can be mounted on a helmet

IP68
↓ 3m

Specification

	High: 185 Low: 70 Flashing: 180
	117 Metres
	8-30 Hour runtime
MODE	High/Low/Flashing
	4 x AA batteries (not included)
	IP68
	172x47mm Ø
	140g
CODE	SA-SIGMA-4AA Previously: NSSAFA-FLA-4AA

Supplied with: Wrist strap
Optional helmet clips are available

CERTIFICATION:



Scan for multi language information

Class I Div 1&2 Grp ABCD
Class II Div 1&2 Grp EFG
Class III Temp Code: T4
FILE NO: E324236

Gas: II 1 G Ex ia IIC T4 IP68
DEMKO 13
ATEX 1205039X

Gas: Ex ia IIC T4 Ga
IECEx UL13.0060X