



TITAN ATEX 360° Portable Light

Circular LED light, portable lamp or fixed lighting



Outstanding thermal management since the LED engine is attached directly to the top and bottom cover, acting as a heat sink.



Individual or daisy chain connection

Features:

- ATEX certificated Gas Zone 1 and Dust Zone 21
- Ideal for indoors or outdoors applications
- High light intensity with no glare effect
- 180° or 360° illumination
- IK08 High strength Aluminium housing
- Tempered borosilicate glass tube
- Individual or daisy chain connection
- IK08 + IP66 Rating
- Explosion proof
- Operating temperature -40°C to +50°C

Accessories:

	Protective Grid		Mounting Bracket		Antistatic Protective peel off Foil
	Vertical Cable Hanging Set		Horizontal Cable Hanging Set		Hook Eye Set
	M20x1.5 ø7-12mm		M20x1.5 ø10-15mm		Ex Stopping Plug M20x1.5

	Specification			
	2300	3000	3000	3500
	360°	360°	360°	180° or 360°
	20-30V AC 20-30V DC	28-48V AC 38-60V DC	90-130V AC 90-130V AC	210-250V AC
NOMINAL VOLTAGE	24V AC	42V AC	110V AC	230V AC
WATT	20W	25W	25W	30W
	IP66 + IP67			
	380x125x300mm			
	2.3kg			
CODE	SA-TITAN-24V	SA-TITAN-42V	SA-TITAN-110V	SA-TITAN-230V

CERTIFICATION:



ATEX Zone 1, 2 & 21, 22
 Ⓜ II 2G Ex db op is IIC T6 Gb;
 Ⓜ II 2D Ex tb op is IIIC T85°C Db
 EXA 16 ATEX 0069X
 IECEx EXA 18.0006X



Scan for multi language information